

# DECLARATION OF PERFORMANCE



## fermacell Gypsum Fibreboard Nr. FC-0001

1. Unique identification code of the produkt-type **FC-0001**
2. Intended use **Gypsum-based dry construction board for interior application on walls, ceilings and floors**
3. Manufacturer **Fermacell GmbH  
Düsseldorfer Landstraße 395  
D-47259 Duisburg  
Tel. +49 800 5235665  
Fax +49 800 5356578  
E-Mail info@xella.com**
5. System of assesement and verification of constancy of performance **System 3**
6. European Assessment Document  
European technical evaluation  
Technical evaluation body  
Notified body **CUAP 05.04/04  
ETA 03/0050  
Deutsches Institut für das Bauwesen, Berlin  
MPA Braunschweig (0761-CPR)**
7. Declared performance

Essential Characteristics	Performance	Essential Characteristics	Performance
flexural strength	≥5,8 N/mm <sup>2</sup>	thickness	10-25 mm +/-0,2mm Typ C1
fire behavior	A2-s1, d0 A2fl K10	moisture content	1,0 - 1,5%
shock resistance	11mm/mm board thickness	Stretching / shrinking behavior	+/- 0,33mm/m
soundproofing	NPD	water absorption	Typ GF-W2
thermal conductivity	0,32 W/mK	surface hardness	Typ GF-I
Water vapor transmission resistance factor	13		

The performance of the product above corresponds to the stated performance (s). The above-mentioned producer is solely responsible for the preparation of the service declaration in accordance with Regulation (EU) No 305/2011.

Signed for the manufacturer and on behalf of the manufacturer of:

Duisburg, 01.09.2017

Dr. Jörg Brinkmann (CEO)